

衛星系列產品

定向耦合器



2路								
Model #	Frequency Range (MHz)	Insertion Loss		Isolation		Return Loss		
		In-Out	In-Tap	Out-Tap	Port-Port	In	Out	Port
SDC-212	10-40	2.7	12	28	22	10	15	10
	40-950	2.7	12.5	25	20	12	15	12
	950-1450	3.5	13	22	18	10	12	12
	1450-2150	5.0	15	20	18	8	12	10
	2150-2350	6.0	16	20	16	8	12	8
SDC-216	10-40	1.7	16.5	25	25	12	16	10
	40-950	1.7	17	28	18	15	16	12
	950-1450	2.5	18	25	16	15	16	12
	1450-2150	3.0	19	22	16	12	12	12
	2150-2350	4.0	20	22	16	12	12	10
SDC-220	10-40	1.7	20	30	20	15	18	10
	40-950	1.7	20.5	30	20	16	18	12
	950-1450	2.5	21	28	16	15	18	10
	1450-2150	3.0	22	25	16	14	15	12
	2150-2350	3.5	23	25	16	12	14	10
SDC-224	10-40	1.0	24	32	20	18	18	10
	40-950	1.2	24.5	32	18	18	18	12
	950-1450	1.8	26	30	16	15	18	12
	1450-2150	2.5	27	25	16	12	16	12
	2150-2350	3.0	27	25	16	12	15	10
SDC-228	10-40	1.0	28	40	20	18	18	10
	40-950	1.2	28.5	35	18	18	18	12
	950-1450	1.5	29	32	16	15	18	12
	1450-2150	2.0	30	28	16	12	15	12
	2150-2350	2.5	30	26	16	12	15	10