

16 IN 1 調變主機-可調式

Frequency Range	47 ~ 860MHz (Any one channel)
Output Level	$\geq 105\text{dB}\mu\text{V}$
Output Level Adjustment Range	0 ~ -20dB (Variable)
Video to Audio Carrier	-10dB ~ -30dB adjustable
Output Impedance	75 Ω
Spurious Output Suppression	$\geq 60\text{dB}$
Frequency Accuracy	$\leq \pm 5\text{KHz}$ (VHF) , $\leq \pm 10\text{KHz}$ (UHF)
Video Output Reflection	$\geq 12\text{dB}$ (VHF) ; $\geq 10\text{dB}$ (UHF)
Video Input Level	1.0Vp-p (87.5% Modulation)
Video Input Impedance	75 Ω
Differential Gain	$\leq 5\%$ (87.5% Modulation)
Differential Phase	$\leq 5^\circ$ (87.5% Modulation)
C/L Delay	$\leq 45\text{ ns}$
Flatness	$\pm 1\text{dB}$
Video Modulator Depth	0 ~ 90% (Variable)
Video S/N	$\geq 55\text{dB}$
Audio Input Level	1Vp-p ($\pm 50\text{KHz}$)
Audio Input Impedance	600 Ω
Audio S/N	$\geq 57\text{dB}$
Audio Pre-weighted	50 μs
Power Supply	AC 110V $\pm 10\%$ 50Hz $\pm 2\text{Hz}$, 50W
Working Temperature	0 ~ 40 $^\circ\text{C}$
Dimensions	19 Inch 4 U housing